



### 1. Description

This procedure describes the repair and complete replacement of a bolted-on plastic fender. Inspection and evaluation requirements are also included.



### 2. Purpose

The purpose of this procedure is to provide industry-accepted requirements for performing high-quality repair of bolted-on plastic fenders. This procedure is intended for use by professionals who are qualified through training and experience.



### 3. Referenced Documents

The following documents are considered part of this procedure by reference.

#### 3.1 Procedures

- PR01 Plastic Repair, Welding
- PR11 Plastic Repair, Adhesive
- PS01 Personnel Safety
- RF01P Surface Preparation

#### 3.2 Other Information

- Product-specific information
- Recycled parts information
- Vehicle-specific repair information



## 4. Equipment And Material Requirements

### 4.1 Plastic Welding Materials

Use plastic welding materials as described in **PR01**.

### 4.2 Adhesive Repair Materials

Use plastic adhesive materials as described in **PR11**.



## 5. Damage Analysis

### 5.1 General Damage

Inspect bolted-on plastic fenders for these types of damage:

- visible damage
- improper previous repairs
- misalignment with adjacent panels
- damaged finish

Determine whether the bolted-on plastic fender should be repaired or replaced. Fender removal may be required to properly assess underside damage.



## 6. Personnel Safety

### 6.1 General Safety

General safety information is in **PS01**.

### 6.2 Plastic Repair Safety

Plastic repair safety information is in **PR01** or **PR11**.



## 7. Environmental Safety

Does not apply.



## 8. Vehicle Protection

### 8.1 Adjacent Areas

Protect glass, upholstery, and other adjacent cosmetic surfaces, as necessary during repairs, removal, or installation.

### 8.2 Anti-Theft Label

Protect the anti-theft label, or other labels, during repair and refinishing operations.



## 9. Repair Procedure

### 9.1 Fender Repair

Select the repair method and perform the repairs.

Before proceeding, decide whether plastic repairs can be made with the fender installed on the vehicle. For removal see **9.2**. For installation see **9.3**.

To repair a bolted-on plastic fender:

- 1. Repair damage using plastic repair welding or adhesive repair procedures.
- 2. Replace trim mounting studs or holes, if necessary.
- 3. Prime all interior and exterior surfaces and other areas damaged by the collision or repairs.
- 4. Apply seam sealers as necessary to seal the joints and restore the appearance. Reprime if required by the product maker.
- 5. Refinish areas damaged by the collision, repairs, or anchoring, as required to restore the appearance. Refinish cosmetic surfaces after all body repairs are complete.
- 6. Install inner splash panels and other parts as required.
- 7. Continue vehicle reassembly.

### 9.2 Fender Removal

To remove a bolted-on plastic fender:

- 1. Protect adjacent panels.
- 2. Loosen or remove the inner splash panel.
- 3. Reposition or remove any attached mechanical parts or wiring.
- 4. Loosen and remove the mounting fasteners. Discard any damaged fasteners.
- 5. Remove the shims, if necessary. Note the placement and number of shims.
- 6. Remove the plastic fender.
- 7. Make the necessary repairs according to the type of damage, if necessary. See **9.1**.

**(cont'd)**



## 9. Repair Procedure (cont'd)

### 9.3 Fender Installation

To install a bolted-on plastic fender:

- 1. Prepare the fender for vehicle options such as antenna, trim, etc., if necessary.
- 2. Install trim mounting studs or drill holes, if necessary.
- 3. Prime all interior and exterior surfaces, if necessary.
- 4. Apply topcoat to panel edges to restore appearance.
- 5. Position and hold the repaired or replacement fender in place.
- 6. Install the fasteners. If the fasteners are being replaced, use fasteners that are the same size, type, and strength as the original fasteners.
- 7. Install the shims, if necessary.
- 8. Adjust the fender to obtain proper alignment to attached and adjacent parts.
- 9. Torque all fasteners in the proper sequence, to the vehicle maker's recommendations.
- 10. Install the inner splash panel and other parts that were removed or repositioned, as required.
- 11. Continue vehicle reassembly.



## 10. Use Of Recycled (Salvage) Parts

### 10.1 Condition Of Salvage Parts

Inspect a salvage bolted-on plastic fender for these defects:

- unrepairable damage
- improper previous repairs

Plan to transfer or replace any required bodyside moldings, stripes, decals, emblems, or other exterior trim.

### 10.2 Preparation Of Salvage Parts

To prepare a salvage, bolted-on plastic fender for installation:

- Remove any trim or moldings that are to be reused or replaced.
- Make any necessary repairs.
- Clean the part to remove dirt, wax, grease, etc.
- Remove excessive paint film thickness.
- Remove or install trim-mounting studs and drill or fill trim-attachment holes, as required.
- Refinish panel edges before installation, to restore appearance.



## 11. Inspection And Testing

### 11.1 Inspection Of A Repaired Or Replaced Fender

After installation, inspect a bolted-on plastic fender for these conditions:

- proper alignment with attached and adjacent parts
- proper operation of adjacent hinged parts
- proper installation of all fasteners
- proper finish appearance and film thickness
- proper operation of attached electrical and electronic parts

Correct any defects.